

Ace Pendant

AC-S + ■ △

DESCRIPTION

ACE responds to market trends in the optimal pursuit of balance between efficiency, aesthetics, and technology. Simple forms merge with the most advanced electronic offerings for contemporary lighting. ACE boasts innovative features, refined and current finishes. It can be installed as a suspension, wall, or ceiling fixture and can be combined with other components to expand its range of applications. It comes in two sizes, with Led boards of different power, available in matte black, gold, and bronze finishes. Both On/Off and dimmable solutions are available.




PRODUCTS CHARACTERISTICS

installation type	Pendant
material	aluminum
Finish	Anodised
Colour	Black
Power	9,5 W
Lumen output - Full emission	max 560 lm
Efficacy	max 59 lm/W

* Code to complete

Colour	■	CCT	△
Black	B	2700 K	1
		3000 K	2
		4000 K	3



ELECTRICAL CHARACTERISTICS

feeding	350mA
Insulation class	Class III

MECHANICAL CHARACTERISTICS

product IP rate	IP20
-----------------	------

Ace Pendant

AC-S + ■ △

LED SOURCE DETAILS

led source type	SMD Led
Light source coding	RG0
Light temperature	2700 K
CRI	CRI > 80
SDCM	


LIGHTING DETAILS

emission	diffused
optic	180°

COMPONENTS

Rosone - 220-240Vac, alimentatore incluso

BSS02AB + ■ △



Colour	■	Control	* Code to complete △
nero	B	DALI	DA
bianco	W	On/Off	NF
		Push	PU

Rosone Trimmed - 220-240Vac, alimentatore incluso

BSS04AB + ■ △



Colour	■	Control	* Code to complete △
nero	B	DALI	DA
bianco	W	On/Off	NF
		Push	PU

Ace Pendant

AC-S + 