


Segno System

BHD64420DA - Module for pendant or ceiling mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

DESCRIPTION

Segno System allow to create linear lighting effects without breaks. It is designed in different configuration to different ceiling, pendant, wall, trimless recessed mounting. It is composed by lighting modules which must be completed with the appropriate mounting accessories as a function of the type of installation to be carried out. The installation of the lighting modules in a continuous line is achieved thanks to the special mechanical joints "Junction Driven" which ensure better precision in the alignment of the bars. The lighting modules are pre-wired and can be equipped with different power systems, allowing full compatibility with all electrical systems. The lighting modules are already complete with optics modules (lenses+led) which are fixed by magnets, and the connection is made thanks to a quick connection plug. The optical modules are preassembled and protect the LEDs from any possible accidental contact even during the installation.



Switch

DALI

PRODUCTS CHARACTERISTICS

installation type	Linear light		
material	Aluminum		
Finish	Painted		
Color	White		
Power	48 W		
Lumen output - Direct emission	8275 lm		
Efficacy	172 lm/W		
Dimensions	2250 mm.		
		H 110	2250

ELECTRICAL CHARACTERISTICS

feeding	
driver	
Insulation class	

220÷240 V DALI Class I

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



Segno System

BHD64420DA - Module for pendant or ceiling mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

MECHANICAL CHARACTERISTICS			
product IP rate	IP20		
LED SOURCE DETAILS			
led source type Photobiological risk	SMD Led RG 1 Low risk (IEC 62471)		
LED brand	TCI or equivalent		
Service lifetime	L80 / B20 - 80.000 h.		
Light temperature CRI	3000 K CRI > 92		
SDCM	<3		
DRIVER CHARACTERISTICS			
driver	DALI		
LIGHTING DETAILS			
emission	Downlight		
Beam angle - direct	90°		
Ť			
PHOTOMETRIC			

