


Segno System

BWD16540 - Module for wall mounting - downlight - single switch - 573 mm. - 12 W - 4000 K / 4000 K / CRI > 91

DESCRIPTION

Segno System allow to create linear lighting effects without breaks. It is designed in different configuration to different ceiling, pendant, wall, trimless recessed mounting. It is composed by lighting modules which must be completed with the appropriate mounting accessories as a function of the type of installation to be carried out. The installation of the lighting modules in a continuous line is achieved thanks to the special mechanical joints "Junction Driven" which ensure better precision in the alignment of the bars. The lighting modules are pre-wired and can be equipped with different power systems, allowing full compatibility with all electrical systems. The lighting modules are already complete with optics modules (lenses+led) which are fixed by magnets, and the connection is made thanks to a quick connection plug. The optical modules are preassembled and protect the LEDs from any possible accidental contact even during the installation.



Switch On÷Off

PRODUCTS CHARACTERISTICS

Wall Mounting installation type **Aluminum** material Finish **Painted** Color White 12 W Power Lumen output - Direct emission 1585 lm Efficacy 132 lm/W **Dimensions** 573 mm.

∐ 110 ______ 55 573

ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver On÷Off
Insulation class Class I





Segno System

BWD16540 - Module for wall mounting - downlight - single switch - 573 mm. - 12 W - 4000 K / 4000 K / 2000 K

MECHANICAL CHARACTERISTICS

product IP rate

IP20

SMD Led

LED SOURCE DETAILS

led source type

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand TCl or equivalent
Service lifetime L80 / B20 - 80.000 h.

Light temperature 4000 K
CRI CRI > 91
SDCM <3

DRIVER CHARACTERISTICS

driver On÷Off

LIGHTING DETAILS

emission Downlight
Beam angle - direct 120°

PHOTOMETRIC

