


Segno System

BWU65540DA – Module for wall mounting – uplight / downlight – single switch – 1691 mm. – 36+12 W – 4000 K / 4000 K / CRI > 91

DESCRIPTION

Segno System allow to create linear lighting effects without breaks. It is designed in different configuration to different ceiling, pendant, wall, trimless recessed mounting. It is composed by lighting modules which must be completed with the appropriate mounting accessories as a function of the type of installation to be carried out. The installation of the lighting modules in a continuous line is achieved thanks to the special mechanical joints "Junction Driven" which ensure better precision in the alignment of the bars. The lighting modules are pre-wired and can be equipped with different power systems, allowing full compatibility with all electrical systems. The lighting modules are already complete with optics modules (lenses+led) which are fixed by magnets, and the connection is made thanks to a quick connection plug. The optical modules are preassembled and protect the LEDs from any possible accidental contact even during the installation.



Switch

DALI

PRODUCTS CHARACTERISTICS

installation type	Wall Mounting	
material	Aluminum	
Finish	Painted	
Color	White	
Power	36+12 W	
Lumen output - Direct emission	4790 lm	
Lumen output - Indirect emission	1865 lm	
Lumen output – Full emission	6655 lm	
Efficacy	139 lm/W	
Dimensions	1691 mm.	110 55 1691

ELECTRICAL CHARACTERISTICS

feeding	
driver	
Insulation class	

220÷240 V DALI Class I

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



Segno System

BWU65540DA – Module for wall mounting – uplight / downlight – single switch – 1691 mm. – 36+12 W – 4000 K / 4000 K / CRI > 91

MECHANICAL CHARACTERISTICS		
product IP rate	IP40	
LED SOURCE DETAILS		
led source type Photobiological risk LED brand Service lifetime Light temperature CRI SDCM	SMD Led RG 1 Low risk (IEC 62471) TCl or equivalent L80 / B20 - 80.000 h. 4000 K CRI > 91 < 3	
DRIVER CHARACTERISTICS		
driver	DALI	
LIGHTING DETAILS		
emission Beam angle - direct	uplight/downlight (single switch) 120°	
PHOTOMETRIC		

