


Segno System

BWU65540 - Module for wall mounting - uplight / downlight - single switch - 1691 mm. - 36+12 W - 4000 K / 4000 K / CRI > 91

DESCRIPTION

Segno System allow to create linear lighting effects without breaks. It is designed in different configuration to different ceiling, pendant, wall, trimless recessed mounting. It is composed by lighting modules which must be completed with the appropriate mounting accessories as a function of the type of installation to be carried out. The installation of the lighting modules in a continuous line is achieved thanks to the special mechanical joints "Junction Driven" which ensure better precision in the alignment of the bars. The lighting modules are pre-wired and can be equipped with different power systems, allowing full compatibility with all electrical systems. The lighting modules are already complete with optics modules (lenses+led) which are fixed by magnets, and the connection is made thanks to a quick connection plug. The optical modules are preassembled and protect the LEDs from any possible accidental contact even during the installation.



Switch

On÷Off

PRODUCTS CHARACTERISTICS

installation type	Wall Mounting		
material	Aluminum		
Finish	Painted		
Color	White		
Power	36+12 W		
Lumen output - Direct emission	4790 lm		
Lumen output – Indirect emission	1865 lm		
Lumen output – Full emission	6655 lm		
Efficacy	139 lm/W		
Dimensions	1691 mm.	H∏ 110	1691

ELECTRICAL CHARACTERISTICS

feeding driver Insulation class 220÷240 V On÷Off Class I

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



Segno System

BWU65540 - Module for wall mounting - uplight / downlight - single switch - 1691 mm. - 36+12 W - 4000 K / 4000 K / CRI > 91

MECHANICAL CHARACTERISTICS		
product IP rate	IP40	
LED SOURCE DETAILS		
led source type	SMD Led	
Photobiological risk	RG 1 Low risk (IEC 62471)	
LED brand	TCI or equivalent	
Service lifetime Light temperature	L80 / B20 - 80.000 h. 4000 K	
CRI	4000 K CRI > 91	
SDCM	< 3	
DRIVER CHARACTERISTICS		
driver	On÷Off	
LIGHTING DETAILS		
emission	uplight/downlight (single switch)	
Beam angle - direct	120°	
PHOTOMETRIC		



