

Segno System Trimless


CTD32440DA - Module for trimless recessed mounting - downlight - single switch - 1131 mm. - 24 W - 3000 K / 3000 K / CRI > 92

DESCRIPTION

Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.

Switch

DALI



PRODUCTS CHARACTERISTICS

installation type	Linear light	
material	Aluminum	
Finish	Painted	
Color	White	
Power	24 W	
Lumen output - Direct emission	3050 lm	
Efficacy	127 lm/W	
Dimensions	1131 mm.	
		<u></u> 85,75 <u>:</u>

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	DALI
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP20



Segno System Trimless

CTD32440DA - Module for trimless recessed mounting - downlight - single switch - 1131 mm. - 24 W - 3000 K / 3000 K / CRI > 92

LED SOURCE DETAILS

led source type	SMD Led
Photobiological risk	RG 1 Low risk (IEC 62471)
LED brand	TCl or equivalent
Service lifetime	L80 / B20 - 80.000 h.
Light temperature	3000 K
CRI	CRI > 92
SDCM	< 3
DRIVER CHARACTERISTICS	

driver

DALI

LIGHTING DETAILS

Beam angle – direct 120°	emission	Downlight
	Beam angle – direct	120°

PHOTOMETRIC

