

# Segno System Trimless


CTD32520DA - Module for trimless recessed mounting - downlight - single switch - 1131 mm. - 24 W - 4000 K / 4000 K / CRI > 91

### DESCRIPTION

Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.

Switch

DALI



#### **PRODUCTS CHARACTERISTICS**

installation type	Linear light	
material	Aluminum	
Finish	Painted	
Color	White	
Power	24 W	
Lumen output - Direct emission	4270 lm	
Efficacy	178 lm/W	
Dimensions	1131 mm.	
		<u></u> 85,75 <u></u> 55 1131

#### **ELECTRICAL CHARACTERISTICS**

feeding	220÷240 V
driver	DALI
Insulation class	Class I

### MECHANICAL CHARACTERISTICS

product IP rate

IP20

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



# Segno System Trimless

CTD32520DA - Module for trimless recessed mounting - downlight - single switch - 1131 mm. - 24 W - 4000 K / 4000 K / CRI > 91

## LED SOURCE DETAILS

Service lifetime Light temperature CRI SDCM DRIVER CHARACTERISTICS	L80 / B20 - 80.000 h. 4000 K CRI > 91 < 3	
led source type Photobiological risk LED brand	SMD Led RG 1 Low risk ( IEC 62471 ) TCI or equivalent	

#### LIGHTING DETAILS

emission	Downlight
Beam angle - direct	90°

#### PHOTOMETRIC

