


Segno System Trimless

CTD32560CA - Module for trimless recessed mounting - downlight - single switch - 1131 mm. - 24 W - 4000 K / 4000 K / CRI > 91

DESCRIPTION


Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.

Switch Casambi



PRODUCTS CHARACTERISTICS

installation type Linear light **Aluminum** material Finish **Painted** Color White Power 24 W 4445 lm Lumen output - Direct emission 185 lm/W Efficacy 1131 mm. **Dimensions**



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Casambi
Insulation class Class I

MECHANICAL CHARACTERISTICS

product IP rate IP20





Segno System Trimless

CTD32560CA - Module for trimless recessed mounting - downlight - single switch - 1131 mm. - 24 W - 4000 K / 4000 K / CRI > 91

LED SOURCE DETAILS

led source type SMD Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand TCl or equivalent
Service lifetime L80 / B20 - 80.000 h.

Light temperature 4000 K
CRI CRI > 91
SDCM <3

DRIVER CHARACTERISTICS

driver Casambi

LIGHTING DETAILS

emission Downlight
Beam angle - direct Dual Asymmetric

PHOTOMETRIC

