




Segno System Trimless

CTD48410PU - Module for trimless recessed mounting - downlight - single switch - 1691 mm. - 36 W - 3000 K / 3000 K / CRI > 92

DESCRIPTION


Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.

Switch Push



PRODUCTS CHARACTERISTICS

installation type Linear light **Aluminum** material **Painted** Finish Color White Power 36 W 6395 lm Lumen output - Direct emission 178 lm/W Efficacy 1691 mm. **Dimensions**



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V driver Push Insulation class Class I

MECHANICAL CHARACTERISTICS

product IP rate IP20





Segno System Trimless

CTD48410PU - Module for trimless recessed mounting - downlight - single switch - 1691 mm. - 36 W - 3000 K / 3000 K / CRI > 92

LED SOURCE DETAILS

led source type SMD Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand TCI or equivalent
Service lifetime L80 / B20 - 80.000 h.
Light temperature 3000 K

Light temperature 3000 K
CRI CRI > 92
SDCM <3

DRIVER CHARACTERISTICS

driver Push

LIGHTING DETAILS

emission

Beam angle - direct

UGR

Downlight

60°

<19

PHOTOMETRIC

