



Segno System Trimless


CTD64410H1 - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

DESCRIPTION

Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.


Switch

Emergency 1 h.



PRODUCTS CHARACTERISTICS

installation type Linear light **Aluminum** material Finish **Painted** Color White Power 48 W 8520 lm Lumen output - Direct emission 178 lm/W Efficacy Dimensions 2250 mm.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Emergenza 1 h.
Insulation class Class I

MECHANICAL CHARACTERISTICS

product IP rate IP20





Segno System Trimless

CTD64410H1 - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

LED SOURCE DETAILS

led source type SMD Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand TCI or equivalent
Service lifetime L80 / B20 - 80.000 h.
Light temperature 3000 K

Light temperature 3000 K
CRI CRI > 92
SDCM <3

DRIVER CHARACTERISTICS

driver Emergenza 1 h.

LIGHTING DETAILS

emission Downlight
Beam angle - direct 60°
UGR < 19

PHOTOMETRIC

