




# Segno System Trimless

CTD64420CA - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

### **DESCRIPTION**


Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.

Switch Casambi



### PRODUCTS CHARACTERISTICS

installation type Linear light **Aluminum** material **Painted** Finish Color White Power 48 W 8275 lm Lumen output - Direct emission 172 lm/W Efficacy 2250 mm. **Dimensions** 



### **ELECTRICAL CHARACTERISTICS**

feeding 220÷240 V
driver Casambi
Insulation class Class I

## MECHANICAL CHARACTERISTICS

product IP rate IP20





# Segno System Trimless

CTD64420CA - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

### LED SOURCE DETAILS

led source type SMD Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand TCl or equivalent
Service lifetime L80 / B20 - 80.000 h.

Light temperature 3000 K
CRI CRI > 92
SDCM < 3

### **DRIVER CHARACTERISTICS**

driver Casambi

### LIGHTING DETAILS

emission Downlight
Beam angle - direct 90°

### **PHOTOMETRIC**

