

### Segno System Trimless

**CTD64440CA** - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

#### DESCRIPTION

**Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.**


Switch

**Casambi**



#### PRODUCTS CHARACTERISTICS

installation type	<b>Linear light</b>
material	<b>Aluminum</b>
Finish	<b>Painted</b>
Color	<b>White</b>
Power	<b>48 W</b>
Lumen output - Direct emission	<b>6095 lm</b>
Efficacy	<b>127 lm/W</b>
Dimensions	<b>2250 mm.</b>



#### ELECTRICAL CHARACTERISTICS

feeding	<b>220÷240 V</b>
driver	<b>Casambi</b>
Insulation class	<b>Class I</b>

#### MECHANICAL CHARACTERISTICS

product IP rate	<b>IP20</b>
-----------------	-------------

### Segno System Trimless

**CTD64440CA** - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

#### LED SOURCE DETAILS

led source type	<b>SMD Led</b>
Photobiological risk	<b>RG 1 Low risk ( IEC 62471 )</b>
LED brand	<b>TCl or equivalent</b>
Service lifetime	<b>L80 / B20 - 80.000 h.</b>
Light temperature	<b>3000 K</b>
CRI	<b>CRI &gt; 92</b>
SDCM	<b>&lt; 3</b>

#### DRIVER CHARACTERISTICS

driver	<b>Casambi</b>
--------	----------------

#### LIGHTING DETAILS

emission	<b>Downlight</b>
Beam angle - direct	<b>120°</b>

#### PHOTOMETRIC

