

## Segno System Trimless

**CTD64460DA** - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

### DESCRIPTION

Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.



DALI



installation type	Linear light	
material	Aluminum	
Finish	Painted	
Color	White	
Dower	48 W	
umen output - Direct emission	8605 lm	
Efficacy	179 lm/W	
Dimensions	2250 mm.	
		<u></u> 85,75 <u></u> 55 85,75 <u></u> 2250

### ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	DALI
Insulation class	Class I

## MECHANICAL CHARACTERISTICS

product IP rate

IP20



# Segno System Trimless

**CTD64460DA** - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 3000 K / 3000 K / CRI > 92

## LED SOURCE DETAILS

led source type	SMD Led	
Photobiological risk	RG 1 Low risk ( IEC 62471 )	
LED brand	TCI or equivalent	
Service lifetime	L80 / B20 - 80.000 h.	
Light temperature	3000 K	
CRI	CRI > 92	
SDCM	< 3	

#### DRIVER CHARACTERISTICS

driver

DALI

### LIGHTING DETAILS

emission Beam angle - direct Downlight Dual Asymmetric

### PHOTOMETRIC

