



# Segno System Trimless


CTD64520H1 - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 4000 K / 4000 K / CRI > 91

### **DESCRIPTION**

Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.


Switch

Emergency 1 h.



#### PRODUCTS CHARACTERISTICS

installation type Linear light **Aluminum** material **Painted** Finish Color White Power 48 W 8540 lm Lumen output - Direct emission 178 lm/W Efficacy Dimensions 2250 mm.



### **ELECTRICAL CHARACTERISTICS**

feeding 220÷240 V
driver Emergenza 1 h.
Insulation class Class I

## **MECHANICAL CHARACTERISTICS**

product IP rate IP20





# Segno System Trimless

CTD64520H1 - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 4000 K / 4000 K / CRI > 91

### LED SOURCE DETAILS

led source type SMD Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand TCl or equivalent
Service lifetime L80 / B20 - 80.000 h.

Light temperature 4000 K
CRI CRI > 91
SDCM <3

### **DRIVER CHARACTERISTICS**

driver Emergenza 1 h.

#### LIGHTING DETAILS

emission Downlight
Beam angle - direct 90°

## **PHOTOMETRIC**

