

# Segno System Trimless


CTD64550H1 - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 4000 K / 4000 K / CRI > 91

### DESCRIPTION

Segno Trimless is a system for continuous linear recessed lighting, which can be simply and fastly installed trimless. The ceiling finishing operations are completed before the electrical installation, which can be carried out in total cleanliness and without powder. The trimless recessed versions are made from structural modules that are installed on false ceiling frames thanks to the "Click & Lock" snap spring system.

Switch

Emergency 1 h.



#### **PRODUCTS CHARACTERISTICS**

installation type	Linear light	
material	Aluminum	
Finish	Painted	
Color	White	
Power	48 W	
Lumen output - Direct emission	8630 lm	
Efficacy	180 lm/W	
Dimensions	2250 mm.	
		<u></u> 85,75 <u></u> 55 2250

#### **ELECTRICAL CHARACTERISTICS**

feeding	220÷240 V
driver	Emergenza 1 h.
Insulation class	Class I

### MECHANICAL CHARACTERISTICS

product IP rate

IP20

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



# Segno System Trimless

**CTD64550H1** - Module for trimless recessed mounting - downlight - single switch - 2250 mm. - 48 W - 4000 K / 4000 K / CRI > 91

## LED SOURCE DETAILS

led source type	SMD Led
Photobiological risk	RG 1 Low risk ( IEC 62471 )
LED brand	TCI or equivalent
Service lifetime	L80 / B20 - 80.000 h.
Light temperature	4000 K
CRI	CRI > 91
SDCM	< 3

### **DRIVER CHARACTERISTICS**

driver

Emergenza 1 h.

### LIGHTING DETAILS

emission Downlight Beam angle – direct Asymmetric

### PHOTOMETRIC

