

Brick

EST51001 - 15 W / 3000 K / CRI >80


DESCRIPTION

Brick is an outdoor projector made of painted die-cast aluminum. It distinguishes itself for two possible installation ways: ground or wall installation. Brick is suitable therefore for the vertical lighting of facades and walls creating grazing light effects or wide beams of light projected horizontally. The shape of the body of the fixture allows to shield the light to limit direct glare; the protection glass is flush mounted with the body to prevent stagnation of dust on its surface. Complete with driver included in the body and high efficiency CoB led, Brick can be quickly installed thanks to its fixing base, which can be separated from the body and already drilled for In/Out wiring.



PRODUCTS CHARACTERISTICS

installation type material Color Power Lumen output - Full emission net weight Wall and Ceiling Mounted Aluminum die casting Gray 15 W 660 lm 2,03 kg.



ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On÷Off
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP65

PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.



Brick

EST51001 - 15 W / 3000 K / CRI >80

LED SOURCE DETAILS

led source type	CoB Led
Light source connection Light temperature	LED 3000 К
CRI	CRI >80

LIGHTING DETAILS

emission	Indirect
optic	90°

PHOTOMETRIC

