

Brick

Power

net weight

EST51002 - 15 W / 3000 K / CRI >80

DESCRIPTION

Brick is an outdoor projector made of painted die-cast aluminum. It distinguishes itself for two possible installation ways: ground or wall installation. Brick is suitable therefore for the vertical lighting of facades and walls creating grazing light effects or wide beams of light projected horizontally. The shape of the body of the fixture allows to shield the light to limit direct glare; the protection glass is flush mounted with the body to prevent stagnation of dust on its surface. Complete with driver included in the body and high efficiency CoB led, Brick can be quickly installed thanks to its fixing base, which can be separated from the body and already drilled for In/Out wiring.




PRODUCTS CHARACTERISTICS

installation type Wall and Ceiling

Mounted material Aluminum die casting Color

White 15 W Lumen output - Full emission 660 lm 2,03 kg.



ELECTRICAL CHARACTERISTICS

220÷240 V feeding driver On÷Off Insulation class Class I

MECHANICAL CHARACTERISTICS

product IP rate IP65





Brick

EST51002 - 15 W / 3000 K / CRI >80

LED SOURCE DETAILS

led source type	CoB Led
Light source connection	LED
Light temperature	3000 K
CRI	CRI >80

LIGHTING DETAILS

emission	Indirect
optic	90°

PHOTOMETRIC

