

### Win

**EST51119** - 12 W - Up / Down + Diffuser / 3000 K / CRI >80

#### DESCRIPTION

**Win** is made of die-cast aluminum and is suitable for a grazing lighting of walls and facades; it is suitable for wall installation and is equipped with an integrated driver and high efficiency LED sources. **Win** is available in the three colours white, grey and anthracite, and in the two different versions up/down and up/down with diffuser; both configurations are characterized by adjustable flaps, positioned in correspondence with both up and down emissions of the luminaire, which allow to gradually darken the light beams emitted, personalizing the luminous effect on the wall. The version with diffuser has an additional third led which, through the opal front glass, illuminates the surrounding area with soft and diffused light. **Win** can be installed on the wall thanks to the base independent from the body which facilitates the correct alignment of the fixing.



#### PRODUCTS CHARACTERISTICS

installation type	<b>Wall and Ceiling Mounted</b>
material	<b>Aluminum die casting</b>
Color	<b>Anthracite</b>
Power	<b>12 W</b>
Lumen output - Full emission	<b>490 lm</b>
net weight	<b>1,3 kg</b>

#### ELECTRICAL CHARACTERISTICS

feeding	<b>220÷240 V</b>
driver	<b>On÷Off</b>
Insulation class	<b>Class I</b>

#### MECHANICAL CHARACTERISTICS

product IP rate	<b>IP54</b>
IK	<b>IK06</b>

#### LED SOURCE DETAILS

led source type	<b>Power Led</b>
Light source connection	<b>LED</b>
Light temperature	<b>3000 K</b>
CRI	<b>CRI &gt;80</b>

### Win

EST51119 - 12 W - Up / Down + Diffuser / 3000 K / CRI >80

### LIGHTING DETAILS

emission  
optic

**Direct / Indirect / Diffused**  
**0°-100°**

### PHOTOMETRIC

