

Win

EST51121 - 12 W - Up / Down + Diffuser / 3000 K / CRI >80

DESCRIPTION

Win is made of die-cast aluminum and is suitable for a grazing lighting of walls and facades; it is suitable for wall installation and is equipped with an integrated driver and high efficiency LED sources. Win is available in the three colours white, grey and anthracite, and in the two different versions up/down and up/down with diffuser; both configurations are characterized by adjustable flaps, positioned in correspondence with both up and down emissions of the luminaire, which allow to gradually darken the light beams emitted, personalizing the luminous effect on the wall. The version with diffuser has an additional third led which, through the opal front glass, illuminates the surrounding area with soft and diffused light. Win can be installed on the wall thanks to the base independent from the body which facilitates the correct alignment of the fixing.



PRODUCTS CHARACTERISTICS

installation type	Wall and Ceiling Mounted
material	Aluminum die casting
Color	White
Power	12 W
Lumen output - Full emission	490 lm
net weight	1,3 kg

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On÷Off
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate	IP54
IK	IK06

LED SOURCE DETAILS

led source type	Power Led
Light source connection	LED
Light temperature	3000 K
CRI	CRI >80

Win

EST51121 - 12 W - Up / Down + Diffuser / 3000 K / CRI >80

LIGHTING DETAILS

emission
optic

Direct / Indirect / Diffused
0°-100°

PHOTOMETRIC

