

### Microled

**EST58121** - 1 W - Rounded / 3000 K / CRI >80

#### DESCRIPTION

To be encased in floors and is watertight. It can be used both indoors and outdoors. Made in aluminium with front AISI 304 steel ring. Protection glass with a slightly satin finish. It comes with an installation kit that includes threaded ring or steel spring on panels and PBT formwork for brickwork installations.



#### PRODUCTS CHARACTERISTICS

installation type	<b>Small Ingrounds</b>
material	<b>Aluminum / AISI 304 stainless steel</b>
Color	<b>Steel</b>
Power	<b>1 W</b>
Lumen output - Full emission	<b>95 lm</b>
Efficacy	<b>150 lm/W</b>
Diameter	<b>ø 23 mm.</b>
net weight	<b>0,02 kg.</b>

#### ELECTRICAL CHARACTERISTICS

feeding	<b>350 mA CC</b>
Insulation class	<b>Class III</b>

#### MECHANICAL CHARACTERISTICS

product IP rate	<b>IP67</b>
-----------------	-------------

#### HOLE RECESS DIMENSIONS

hole recess diameter	<b>ø 19 mm.</b>
----------------------	-----------------

#### LED SOURCE DETAILS

led source type	<b>Power Led</b>
LED current	<b>350 mA</b>
Light temperature	<b>3000 K</b>
CRI	<b>CRI &gt;80</b>

## Microled

EST58121 - 1 W - Rounded / 3000 K / CRI >80

### LIGHTING DETAILS

emission  
luminous effect  
optic

**Direct**  
**Projected**  
**120°**

### PHOTOMETRIC

