

Microled

EST58123 - 1 W - Rounded / 3000 K / CRI >80

DESCRIPTION

To be encased in floors and is watertight. It can be used both indoors and outdoors. Made in aluminium with front AISI 304 steel ring. Protection glass with a slightly satin finish. It comes with an installation kit that includes threaded ring or steel spring on panels and PBT formwork for brickwork installations.



PRODUCTS CHARACTERISTICS

installation type	Small Ingrounds
material	Aluminum / AISI 304 stainless steel
Color	White
Power	1 W
Lumen output - Full emission	95 lm
Efficacy	175 lm/W
Diameter	ø 23 mm.
net weight	0,02 kg.

ELECTRICAL CHARACTERISTICS

feeding	350 mA CC
Insulation class	Class III

MECHANICAL CHARACTERISTICS

product IP rate	IP67
-----------------	-------------

HOLE RECESS DIMENSIONS

hole recess diameter	ø 19 mm.
----------------------	-----------------

LED SOURCE DETAILS

led source type	Power Led
LED current	350 mA
Light temperature	3000 K
CRI	CRI >80

Microled

EST58123 - 1 W - Rounded / 3000 K / CRI >80

LIGHTING DETAILS

emission
luminous effect
optic

Direct
Projected
120°

PHOTOMETRIC

