

# Miniled

EST58133 - 1 W - Rounded / 3000 K / CRI >80

### DESCRIPTION

Miniled is a floor and wall recessed product 1W/ 350 mA; IP67 rating. Aluminium body with front ring in AISI 316 steel, round or square (also available in matt white). Transparent protection glass. 3 optics available. Equipped with PBT housing. Driver not included.




#### **PRODUCTS CHARACTERISTICS**

installation type material Color Power Lumen output - Full emission Efficacy Diameter

net weight

Small Ingrounds Aluminum / AISI 304 stainless steel White 1 W 110 Im 110 Im/W Ø 27 mm. 0,06 kg.



ELECTRICAL CHARACTE	RISTICS	
feeding Insulation class	350 mA CC Class III	
MECHANICAL CHARAC	TERISTICS	
product IP rate	IP67	
PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.
Firenze, Italy	www.panint.it	$10^{-2}$



## Miniled

EST58133 - 1 W - Rounded / 3000 K / CRI >80

hole recess diameter	ø 23 mm.	
LED SOURCE DETAILS		
led source type	Power Led	
LED current	350 mA	
Light temperature	3000 K	
CRI	CRI >80	
LIGHTING DETAILS		
emission	Direct	
luminous effect	Projected	
optic	10°	

#### PHOTOMETRIC

