

# **Planet**

EST80201 - 6 W - Wall mounted - Downlight / 3000 K / CRI > 80

### **DESCRIPTION**


With a rigorously minimal design, Planet combines the extraordinary compactness and solidity of its shape with an innovative spherical lens capable of projecting light in a precise and defined way; the version for ceiling installation creates a wide and clear circular light beam for a performant lighting of paths, porches and covered areas; the version for wall installation illuminates the vertical surface with wide and extraordinarily sharp beams, creating extremely precise and clean grazing light effects. The single emission for wall mounting versions can be installed both for upwards and downwards lighting. Planet is made of die-cast aluminum and is equipped with a drilled fixing bracket for dual in/out connection; this can be installed on the wall or ceiling separately from the optical body for an easier electrical connection to the system and fixing to the wall or ceiling.



#### PRODUCTS CHARACTERISTICS

installation type Wall and Ceiling

Mounted
material Aluminum
Color Anthracite
Power 6 W
Lumen output - Full emission 580 Im



### **ELECTRICAL CHARACTERISTICS**

feeding 220÷240 V
driver On÷Off
Insulation class Class I

### MECHANICAL CHARACTERISTICS





# **Planet**

EST80201 - 6 W - Wall mounted - Downlight / 3000 K / CRI > 80

product IP rate IP65 IK IK06

## LED SOURCE DETAILS

led source type CoB Led Light source connection LED

Service lifetime L80 / B20 - 50.000 h.

Light temperature 3000 K CRI CRI >80

### LIGHTING DETAILS

emission Direct / Indirect optic 100°

## **PHOTOMETRIC**

