

# Boxer

EST81101 - 7 W - Downlight / 3000 K / CRI >80

### DESCRIPTION


Boxer is an outdoor fixture that can be installed on the wall to obtain grazing facades light effects; cubic in shape, it is extremely minimal and it suits to any architectural style by camouflaging itself on the facade. Made of die-cast aluminum, Boxer is available in two different configurations for mono or dual emission; it is equipped with frame kit, supplied as accessories included, to be inserted inside the optical compartment to shape the emission beam, thus obtaining particular grazing light effects. Boxer is available in the finishes matt grey and matt white; it is equipped with driver and CoB led, and can be easily installed thanks to the fixing plate that can be separated from the body.



#### **PRODUCTS CHARACTERISTICS**

installation type
material
Color
Power
Lumen output - Full emission

Wall Mounting Aluminum Gray 7 W 620 Im



ELECTRICAL CHARACTERISTICS			
feeding driver	220÷240 V On÷Off		
MECHANICAL CHARAC	TERISTICS		
product IP rate IK	IP54 IK05		
PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.	
Firenze, Italy	www.panint.it		



# Boxer

EST81101 - 7 W - Downlight / 3000 K / CRI >80

## LED SOURCE DETAILS

led source type	CoB Led
Light source connection	LED
Service lifetime	L80 / B20 - 50.000 h.
Light temperature	3000 K
CRI	CRI >80

### LIGHTING DETAILS

emission	Direct	
optic	110° - 22°	

## PHOTOMETRIC

