

Boxer

EST81201 - 2x 7 W - Uplight / Downlight / 3000 K / CRI > 80

DESCRIPTION


Boxer is an outdoor fixture that can be installed on the wall to obtain grazing facades light effects; cubic in shape, it is extremely minimal and it suits to any architectural style by camouflaging itself on the facade. Made of die-cast aluminum, Boxer is available in two different configurations for mono or dual emission; it is equipped with frame kit, supplied as accessories included, to be inserted inside the optical compartment to shape the emission beam, thus obtaining particular grazing light effects. Boxer is available in the finishes matt grey and matt white; it is equipped with driver and CoB led, and can be easily installed thanks to the fixing plate that can be separated from the body.





PRODUCTS CHARACTERISTICS

installation type material Color Power Lumen output - Full emission Wall Mounting Aluminum White 2x 7 W 1240 lm



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V driver On÷Off

MECHANICAL CHARACTERISTICS

product IP rate IP54
IK IK05





Boxer

EST81201 - 2x 7 W - Uplight / Downlight / 3000 K / CRI >80

LED SOURCE DETAILS

led source type CoB Led Light source connection LED

Service lifetime L80 / B20 - 50.000 h.

Light temperature 3000 K CRI >80

LIGHTING DETAILS

emission Direct / Indirect optic 2x 110° - 22°

PHOTOMETRIC

