



Kart

GRF03111CA - 38 W / 3000 K / CRI > 80

DESCRIPTION

Kart is made of matt white painted aluminium and is equipped with a PMMA diffusing screen which allows to obtain soft and diffused light effects. The curvature of the aluminium body perfectly matches the curvature of the internal PMMA screen to create a single shape with a soft and contemporary design. The high efficiency SMD LED source is powered by the driver integrated in the fixture and can be On/Off or dimmable multifunction 1...10 V, Push, DALI controlled. Kart is available in different sizes and powers and goes well with the suspension versions. Available in dimmable "wireless signal" Bluetooth versions for Pan Digital or Casambi mesh network.




Switch Casambi

PRODUCTS CHARACTERISTICS

installation type Plafone
material Alluminio
Finish Verniciato
Color Bianco
Power 38 W
Lumen output - Direct emission 2290 Im
Lumen output - Full emission 2290 Im
Efficacy

Dimensions 47,5 x 47,5 cm.

net weight 2,6 kg.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Casambi
Insulation class Classe I

MECHANICAL CHARACTERISTICS

product IP rate IP20

Pan International srl Via G. Michelucci, 1 50028 Tavarnelle Val di Pesa Firenze Italy Tel: +39 (0)55 80 59 336/7 Fax: +39 (0)55 80 59 338 panint@panint.it www.panint.it This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



Datasheet

Kart

GRF03111CA - 38 W / 3000 K / CRI > 80

ENERGY CLASSIFICATION





The lamps cannot be changed in the luminaire.

LED SOURCE DETAILS

led source type SMD Led
Light source connection LED
Energy class LED
Light temperature 3000 K
CRI CRI > 80
SDCM

DRIVER CHARACTERISTICS

driver Casambi

LIGHTING DETAILS

emission
optic
UGR

Diretta
130°
\






Kart

GRF03111CA - 38 W / 3000 K / CRI > 80

PHOTOMETRIC



WARRANTY

period 2 years