

Kart

GRF03211DM - 50 W / 3000 K / CRI > 80

DESCRIPTION

Kart is made of matt white painted aluminium and is equipped with a PMMA diffusing screen which allows to obtain soft and diffused light effects. The curvature of the aluminium body perfectly matches the curvature of the internal PMMA screen to create a single shape with a soft and contemporary design. The high efficiency SMD LED source is powered by the driver integrated in the fixture and can be On/Off or dimmable multifunction 1...10 V, Push, DALI controlled. Kart is available in different sizes and powers and goes well with the suspension versions. Available in dimmable "wireless signal" Bluetooth versions for Pan Digital or Casambi mesh network.



Switch

1...10 / Push / DALI

PRODUCTS CHARACTERISTICS

installation type	Plafone	
material	Alluminio	
Finish	Verniciato	
Color	Bianco	
Power	50 W	
Lumen output - Direct emission	2450 lm	
Lumen output – Full emission	2450 lm	
Efficacy	\mathbf{N}	
Dimensions	62,5 x 62,5 cm.	
net weight	2,9 kg.	I 6 [8,5
ő		62,5
		02,0

ELECTRICAL CHARACTERISTICS

feeding	
driver	
Insulation class	

220÷240 V 1...10 / Push / DALI Classe I

MECHANICAL CHARACTERISTICS

product IP rate

IP20

Pan International srl Via G. Michelucci, 1 50028 Tavarnelle Val di Pesa Firenze Italy Tel: +39 (0)55 80 59 336/7 Fax: +39 (0)55 80 59 338 panint@panint.it www.panint.it This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.

kg 5,0



Kart

GRF03211DM - 50 W / 3000 K / CRI > 80

ENERGY CLASSIFICATION



LED SOURCE DETAILS

led source type Light source connection Energy class Light temperature	SMD Led LED LED 3000 K	
CRI	CRI > 80	
SDCM	$\mathbf{\lambda}$	

DRIVER CHARACTERISTICS

driver

1...10 / Push / DALI

LIGHTING DETAILS


emission	Diretta
optic	130°
UGR	λ.



Kart

GRF03211DM - 50 W / 3000 K / CRI > 80

PHOTOMETRIC



WARRANTY

period

2 years