

Play

GRF11111DM - ø 41 cm. - 38 W - 2280 lm / 3000 K / CRI > 80

DESCRIPTION

Play is an aluminium ceiling mounted luminaire in matt white or matt black color painted, equipped with a diffusing opal PMMA screen. Thanks to the SMD LED sources integrated in the body of the device, the lower screen lights up perfectly evenly; Play allows to obtain soft and diffused down light effects and is therefore particularly suitable for illuminating indoor ambients with uniform light, perfectly distributed and free of harsh shadows. Play is complete with drivers integrated into the body of the device and is available in versions OnOff controlled or dimmable 1 ... 10V, Push, DALI controlled. The range is completed by versions for permanent emergency light with 1 hour autonomy, ignition time 0.5 sec. and recharging time 24 h.



Switch

1...10 / Push / DALI

PRODUCTS CHARACTERISTICS

installation type material	ceiling lamps Aluminum	
Finish	Painted	
Color	White	
Power	38 W	
Lumen output - Full emission	2280 lm	
Diameter	ø 41 cm.	
net weight	3,3 kg.	
		e] ۹
		Ø 41
		0
		kg 3,3

ELECTRICAL CHARACTERISTICS

feeding driver Insulation class 220÷240 V 1...10 / Push / DALI Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP20

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it


This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



Play

GRF11111DM - ø 41 cm. - 38 W - 2280 lm / 3000 K / CRI > 80

ENERGY CLASSIFICATION



LED SOURCE DETAILS

led source type Light source connection Light temperature CRI	SMD Led LED 3000 K CRI > 80	
DRIVER CHARACTERISTICS		
driver	110 / Push / DALI	
LIGHTING DETAILS		
luminous effect	diffused light	
optic	110°	

PHOTOMETRIC

Play

GRF11111DM - ø 41 cm. - 38 W - 2280 lm / 3000 K / CRI > 80

