

Play

GRF1121PD - ø 41 cm. - 38 W - 2280 lm / 3000 K / CRI > 80

DESCRIPTION

Play is an aluminium ceiling mounted luminaire in matt white or matt black color painted, equipped with a diffusing opal PMMA screen. Thanks to the SMD LED sources integrated in the body of the device, the lower screen lights up perfectly evenly; Play allows to obtain soft and diffused down light effects and is therefore particularly suitable for illuminating indoor ambients with uniform light, perfectly distributed and free of harsh shadows. Play is complete with drivers integrated into the body of the device and is available in versions OnOff controlled or dimmable 1 ... 10V, Push, DALI controlled. The range is completed by versions for permanent emergency light with 1 hour autonomy, ignition time 0.5 sec. and recharging time 24 h.




Switch

Pan Digital

PRODUCTS CHARACTERISTICS

installation type
material
Finish
Color
Power
Lumen output - Full emission
Diameter
net weight

ceiling lamps
Aluminum
Painted
Black
38 W
2280 lm
ø 41 cm.
3,3 kg.



ELECTRICAL CHARACTERISTICS

feeding
driver
Insulation class

220÷240 V
Pan Digital
Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP20


Play

GRF11121PD - \varnothing 41 cm. - 38 W - 2280 lm / 3000 K / CRI > 80

ENERGY CLASSIFICATION



This luminaire contains built-in LED lamps.



The lamps cannot be changed in the luminaire.

LED SOURCE DETAILS

led source type	SMD Led
Light source connection	LED
Light temperature	3000 K
CRI	CRI > 80

DRIVER CHARACTERISTICS

driver	Pan Digital
--------	--------------------

LIGHTING DETAILS

luminous effect	diffused light
optic	110°

PHOTOMETRIC

Play

GRF11121PD - \varnothing 41 cm. - 38 W - 2280 lm / 3000 K / CRI > 80

