

Dama

GRF12111DM - 42×42 cm. - 38 W - 2280 Im / 3000 K / CRI > 80

DESCRIPTION

Designed in a square shape, Dama is made of matt white or matt black painted aluminium; it is equipped with an opal diffusing screen in PMMA and, thanks to the SMD LED sources integrated in the body of the luminaire, it lights up perfectly evenly; Dama allows to obtain soft and diffused down light effects and is therefore particularly suitable for illuminating indoor ambients with uniform light, perfectly distributed and free of harsh shadows. Dama is complete with drivers integrated into the body of the device and is available in versions On/Off controlled or dimmable 1...10 V, Push, DALI controlled. The range is completed by versions for permanent emergency light with 1 hour autonomy, ignition time 0.5 sec. and charging time 24 h.




Switch

1...10 / Push / DALI

PRODUCTS CHARACTERISTICS

ceiling lamps installation type material Aluminum **Finish** Matt painted Color White 38 W Power Lumen output - Full emission 2280 lm 42×42 cm. **Dimensions** net weight 3,8 kg.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V

driver 1...10 / Push / DALI

Insulation class Class I

MECHANICAL CHARACTERISTICS

product IP rate IP20





Dama

GRF12111DM - 42×42 cm. - 38 W - 2280 Im / 3000 K / CRI > 80

ENERGY CLASSIFICATION



contains built-in LED lamps.



The lamps cannot be changed

LED SOURCE DETAILS

led source type Light source connection Light temperature CRI

SMD Led LED 3000 K CRI > 80

DRIVER CHARACTERISTICS

driver 1...10 / Push / DALI

LIGHTING DETAILS

luminous effect optic

diffused light 110°

PHOTOMETRIC





Dama

GRF12111DM - 42×42 cm. - 38 W - 2280 Im / 3000 K / CRI > 80

