

Dama

GRF12221 - 64 x 64 cm. - 62 W - 3720 lm / 3000 K / CRI > 80

DESCRIPTION

Designed in a square shape, Dama is made of matt white or matt black painted aluminium; it is equipped with an opal diffusing screen in PMMA and, thanks to the SMD LED sources integrated in the body of the luminaire, it lights up perfectly evenly; Dama allows to obtain soft and diffused down light effects and is therefore particularly suitable for illuminating indoor ambients with uniform light, perfectly distributed and free of harsh shadows. Dama is complete with drivers integrated into the body of the device and is available in versions On/Off controlled or dimmable 1...10 V, Push, DALI controlled. The range is completed by versions for permanent emergency light with 1 hour autonomy, ignition time 0.5 sec. and charging time 24 h.



Switch

On÷Off

PRODUCTS CHARACTERISTICS

installation type	ceiling lamps	
material	Aluminum	
Finish	Matt painted	
Color	Black	
Power	62 W	
Lumen output – Full emission	3720 lm	
Dimensions	64 x 64 cm.	
net weight	6,1 kg.	64
		I 6 [9 64

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On÷Off
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP20

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.

ر الاق] 6,1



Dama

GRF12221 - 64×64 cm. - 62 W - 3720 lm / 3000 K / CRI > 80

ENERGY CLASSIFICATION



LED SOURCE DETAILS

led source type	SMD Led	
Light source connection	LED	
Light temperature	3000 K	
CRI	CRI > 80	
DRIVER CHARACTERISTICS		
driver	On / Off	
LIGHTING DETAILS		
luminous effect	diffused light	
optic	110°	
•		
PHOTOMETRIC		



Dama

$GRF12221 - 64 \times 64 \text{ cm.} - 62 \text{ W} - 3720 \text{ Im} / 3000 \text{ K} / CRI > 80$

