

Led Panel Smart

INC56527CA - 30×120 cm. - 36 W - 3000 K / 3000 K / CRI > 90

DESCRIPTION

The Led Panel Smart line is offered in a wide range of versions, in terms of output, colour temperatures and power supplies. All versions are characterized by enhanced luminous emission control to ensure maximum visual comfort, with a UGR value < 19 and the complete absence of flicker.


Switch

Casambi



PRODUCTS CHARACTERISTICS

Light Panels Extruded aluminum White 36 W 3700 Im 103 Im/W 30 x 120 cm. 2,9 kg.



ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	Casambi
Insulation class	Class II

MECHANICAL CHARACTERISTICS

product IP rate IK	IP40 IK03	
PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.
Firenze, Italy	www.panint.it Uploaded 03/10/23 - pg 1 / 2	Uploaded 03/10/23 - pg 1 / 2



Led Panel Smart

INC56527CA - 30×120 cm. - 36 W - 3000 K / 3000 K / CRI > 90

led source type	SMD Led	
Photobiological risk	RG 0 Exempt (IEC 62471)	
Service lifetime	L80 / B20 - 50.000 h.	
Light temperature	3000 K	
CRI	CRI > 90	
DRIVER CHARACTERISTICS		
driver	Casambi	
LIGHTING DETAILS		
Beam angle - direct	120°	
UGR	≤ 19	

PHOTOMETRIC

