

Fast

INC59001 - orizzontale asimmetrico - 3,6 W / 3000 K / CRI > 80

DESCRIPTION

FAST wall-mounted pathway luminaires allow you to illuminate paths with comfortable, glare-free light. All versions are IP65 and can be installed both indoors and outdoors. Always with driver included, Fast is available in different configurations: with asymmetrical optics for direct floor lighting, or with diffusing optics for generally soft light; among these, the "no frame" version is complete with frosted glass mounted on a hidden frame. All 3.6 W versions can be installed directly in the standard 503 box to optimize the system solutions; the aesthetic plates are made of die-cast aluminum, painted in white and gray.





Switch **On:Off**

PRODUCTS CHARACTERISTICS

installation type	Wall Recessed
material	Aluminum die casting
Color	Gray
Power	3,6 W
Lumen output - Full emission	60 lm
net weight	0,30 kg.

Horizontal asymmetric



 0,30

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On:Off
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate	IP65
IK	IK05

Fast

INC59001 - orizzontale asimmetrico - 3,6 W / 3000 K / CRI > 80

LED SOURCE DETAILS

led source type	SMD Led
Service lifetime	L70 / B20 - 50.000 h.
Light temperature	3000 K
CRI	CRI > 80

DRIVER CHARACTERISTICS

driver	On:Off
--------	---------------

LIGHTING DETAILS

emission	Direct
optic	45°
Beam angle - direct	45°

PHOTOMETRIC

