

### Fast

**INC59600EM** - emergency - 3,6 W / 3000 K / CRI > 80

#### DESCRIPTION

**FAST** wall-mounted pathway luminaires allow you to illuminate paths with comfortable, glare-free light. All versions are IP65 and can be installed both indoors and outdoors. Always with driver included, Fast is available in different configurations: with asymmetrical optics for direct floor lighting, or with diffusing optics for generally soft light; among these, the "no frame" version is complete with frosted glass mounted on a hidden frame. All 3.6 W versions can be installed directly in the standard 503 box to optimize the system solutions; the aesthetic plates are made of die-cast aluminum, painted in white and gray.




Switch


On:Off

#### PRODUCTS CHARACTERISTICS

installation type	<b>Wall Recessed</b>
material	<b>Aluminum die casting</b>
Color	<b>White</b>
Power	<b>3,6 W</b>
Lumen output - Full emission	<b>40 lm</b>
net weight	<b>0,30 kg.</b>

Horizontal diffuser



 0,30

#### ELECTRICAL CHARACTERISTICS

feeding	<b>220÷240 V</b>
driver	<b>On:Off</b>
Insulation class	<b>Class I</b>

#### MECHANICAL CHARACTERISTICS

product IP rate	<b>IP20</b>
-----------------	-------------

### Fast

**INC59600EM** - emergency - 3,6 W / 3000 K / CRI > 80

#### LED SOURCE DETAILS

led source type	<b>SMD Led</b>
Service lifetime	<b>L70 / B20 - 50.000 h.</b>
Light temperature	<b>3000 K</b>
CRI	<b>CRI &gt; 80</b>

#### DRIVER CHARACTERISTICS

driver	<b>On+Off</b>
--------	---------------

#### LIGHTING DETAILS

emission	<b>Direct</b>
optic	<b>150°</b>
Beam angle - direct	<b>120°</b>

#### PHOTOMETRIC

