

Lupin

PAR00018 - uplight / downlight - 2x 7 W / 3000 K / CRI > 80

DESCRIPTION

The Lupin luminaire series is made of matt white painted aluminium. The optical bodies are complete with anti-glare front and are equipped with an integrated electronic driver and GU10 lamp socket. Lupine is designed to illuminate with concentrated light effects; the range includes different configurations for wall or ceiling installation and is completed with coordinated versions for suspended installation.

Switch


On+Off



PRODUCTS CHARACTERISTICS

installation type	Ceiling / Wall diffusers
material	Aluminum
Color	White
Power	2x 7 W
Lumen output - Full emission	2x 550 lm
net weight	0,60 kg.

Wall Uplight / Downlight



 0,6

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On+Off
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate	IP20
-----------------	-------------

Lupin

PAR00018 - uplight / downlight - 2x 7 W / 3000 K / CRI > 80

LED SOURCE DETAILS

led source type	LED
Light source connection	GU10
Light temperature	3000 K
CRI	CRI > 80

DRIVER CHARACTERISTICS

driver	On+Off
--------	---------------

LIGHTING DETAILS

emission	Direct / Indirect
----------	--------------------------