

## Orion

PLA00010 - 22 W / 3000 K / CRI > 80

## **DESCRIPTION**

net weight

Orion is realized with a white painted metal structure on which is mounted an opal PMMA screen, convex in shape and made in one piece. Orion is equipped with SMD LED sources and the driver is integrated into the body of the fixtures; it can be installed both on the ceiling and on the wall and is suitable for illuminating rooms with diffused light.

Switch On÷Off



### PRODUCTS CHARACTERISTICS

installation type

material

Color

Power

Lumen output - Full emission

Efficacy

Diameter

Ceiling / Wall diffusers

Aluminum

White


22 W

1430 Im

73 Im/W

Ø 390 mm.

0,80 kg.



## **ELECTRICAL CHARACTERISTICS**

feeding 220÷240 V driver On÷Off Insulation class Class I

### MECHANICAL CHARACTERISTICS

product IP rate IP20



# Orion

PLA00010 - 22 W / 3000 K / CRI > 80

### LED SOURCE DETAILS

led source type	SMD Led
Light source connection	LED
Service lifetime	25.000 h.
Light temperature	3000 K
CRI	CRI > 80

## **DRIVER CHARACTERISTICS**

drivar	On÷Off
driver	On <del>-</del> Ott

## LIGHTING DETAILS

emission	Direct
optic	120°
Beam angle - direct	120°

### **PHOTOMETRIC**

