

Orion

PLA00012 - 18 W / 4000 K / CRI > 80

DESCRIPTION

Orion is realized with a white painted metal structure on which is mounted an opal PMMA screen, convex in shape and made in one piece. Orion is equipped with SMD LED sources and the driver is integrated into the body of the fixtures; it can be installed both on the ceiling and on the wall and is suitable for illuminating rooms with diffused light.

Switch

On÷Off



PRODUCTS CHARACTERISTICS

installation type	Ceiling / Wall diffusers	
material	Aluminum	
Color	White	
Power	18 W	
Lumen output – Full emission	1220 lm	
Efficacy	71 lm/W	
Diameter	ø 330 mm.	
net weight	0,60 kg.	Ø330
		kg 0,60

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On÷Off
Insulation class	Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP20

PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.



Orion

PLA00012 - 18 W / 4000 K / CRI > 80

LED SOURCE DETAILS

led source type	SMD Led
Light source connection	LED
Service lifetime	25.000 h.
Light temperature	4000 K
CRI	CRI > 80

DRIVER CHARACTERISTICS

Ч	river	

On÷Off

LIGHTING DETAILS

emission	Direct	
optic	120°	
Beam angle – direct	120°	

PHOTOMETRIC

