

Orion

PLA00013 - 22 W / 4000 K / CRI > 80

DESCRIPTION

Orion is realized with a white painted metal structure on which is mounted an opal PMMA screen, convex in shape and made in one piece. Orion is equipped with SMD LED sources and the driver is integrated into the body of the fixtures; it can be installed both on the ceiling and on the wall and is suitable for illuminating rooms with diffused light.

Switch On÷Off



PRODUCTS CHARACTERISTICS

installation type
material
Color
Power
Lumen output - Full emission
Efficacy
COLOR
C

Diameter net weight Ceiling / Wall diffusers Aluminum White 22 W 1500 lm 77 lm/W ø 390 mm. 0,80 kg.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V driver On÷Off Insulation class Class I

MECHANICAL CHARACTERISTICS

product IP rate IP20



Orion

PLA00013 - 22 W / 4000 K / CRI > 80

LED SOURCE DETAILS

led source type	SMD Led
Light source connection	LED
Service lifetime	25.000 h.
Light temperature	4000 K
CRI	CRI > 80

DRIVER CHARACTERISTICS

driver	On÷Off
anver	OII. OII

LIGHTING DETAILS

emission	Direct
optic	120°
Beam angle - direct	120°

PHOTOMETRIC

