

Funky

PRJ11212 - 12 W - 850 lm. / 3000 K / CRI >80

DESCRIPTION

The Funky series includes a complete range of IP67 luminaires for the projection of light in outdoor. The range includes three different sizes and powers, all characterized by an extremely clean, minimal and easily camouflaged design; wired with H05RNF neoprene cable, the projectors are made in anodized aluminum and are complete with a 2 mm thick fixing bracket; this is equipped with a graduated ring for aiming adjustment. Funky projectors are equipped with high efficiency CoB drivers and LEDs and are complete with optical lenses with different beam apertures; They are therefore ideal for illuminating objects and architectural elements from a distance with precise accent lighting effects, or to obtain softly diffused grazing light effects on surfaces and facades. The Funky series is completed with a rich range of useful accessories both to solve different types of installation and to control glare.



PRODUCTS CHARACTERISTICS

Efficacy

installation type

material

Finish

Color

Power

Lumen output - Full emission

Outdoor projectors

Aluminum


Anodized

Black

12 W

875 Im

85 lm/W



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver On÷Off
Insulation class Class I





Funky

PRJ11212 - 12 W - 850 lm. / 3000 K / CRI >80

MECHANICAL CHARACTERISTICS

product IP rate

IP67

LED SOURCE DETAILS

led source type Light source connection Service lifetime

CoB Led **LED**

L80 / B20 - 36.000 h.

3000 K Light temperature CRI >80

LIGHTING DETAILS

optic

CRI

20°

PHOTOMETRIC

