

# London

## **RGL03120** - 3 W / 3000 K / CRI > 80

## DESCRIPTION

Wall reading lamp . Painted aluminium body. Adjustable and flexible arm. Integrated high efficiency LED light source. Direct lighting for bright accents. Electronic driver integrated in the fixture. Beam angle 30°.ON/OFF on the base.

Switch

On÷Off



#### **PRODUCTS CHARACTERISTICS**

installation type material Finish Color Power Lumen output – Full emission net weight	Wall Mounting Aluminum Painted Black 3 W 190 Im 0,40 kg.	$\begin{array}{c c} max 35 \\ \hline \\ \hline \\ \hline \\ \hline \\ 2,5 \end{array} \\ \hline \\ \hline \\ \\ \hline \\ \\ \hline \\ \\ \\ \\ 2,5 \end{array} \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$

#### ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	On÷Off
Insulation class	Class II

### MECHANICAL CHARACTERISTICS

product IP rate

IP20

PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.

kg 0,4



# London

RGL03120 - 3 W / 3000 K / CRI > 80

## LED SOURCE DETAILS

Light temperature 3000 K   CRI CRI > 80	led source type	Power Led	
CRI CRI > 80	Light temperature	3000 K	
	CRI	CRI > 80	

### DRIVER CHARACTERISTICS

driver

On÷Off