

Focus

RTB34211 - Rounded - Adj / 4,5 W / 3000 K / CRI >80

DESCRIPTION


Small and performing, the Focus series of recessed minispots create precise accents of light without glare thanks to the backward position of the LED source. In the fixed and adjustable versions, the Focus minispots emit bright light within a sharp and smudge-free beam with only 4.5 W of electricity absorption. The LEDs selected from the first labels and the body entirely made of die-cast aluminum ensure both a long life to the LED source and the constancy of its colorimetric characteristics over time (L80 / B20 at 50,000 hours). Focus is available in a matt white and matt black finish and complete of wired driver.



Switch On÷Off

PRODUCTS CHARACTERISTICS

Recessed Spotlights installation type material Aluminum Color Black Power 4.5 W 195 lm Lumen output - Full emission Efficacy 78 lm/W ø 52 mm. Diameter **Dimensions** h 50 mm. 0,10 kg. net weight



ELECTRICAL CHARACTERISTICS

driver On÷Off

MECHANICAL CHARACTERISTICS

product IP rate IP20

HOLE RECESS DIMENSIONS



Focus

RTB34211 - Rounded - Adj / 4,5 W / 3000 K / CRI >80

hole recess diameter ø 45 mm.

LED SOURCE DETAILS

led source type Power Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED current 700 mA
Light temperature 3000 K
CRI CRI >80
SDCM <3

DRIVER CHARACTERISTICS

driver On÷Off

LIGHTING DETAILS

luminous effect spot optic 20°
Beam angle – direct 20°

PHOTOMETRIC

