

Accent Drop

RTL19110 - Rounded Adjustable - 10 W - 900 lumen / 2700 K / CRI >90

DESCRIPTION


Accent is the downlight equipped with the same LED modules of the Nemo series, it is ideal for all interior design projects where it is necessary to recreate well-defined light accents in the absence of glare. Accent has the LED source set back and completely hidden from view and with a 40 $^\circ$ cut-off it offers maximum visual comfort by creating precise and well-defined uniform light accents. The Drop version is ideal for spot effects on the horizontal plane while the Side version allows you to tilt the optical module for lateral light emissions. All versions are installed in a \emptyset 65 mm recessed hole.



Switch On÷Off

PRODUCTS CHARACTERISTICS

installation type trimmed recessed Aluminum material White Color 10 W Power Lumen output - Full emission 888 Im 89 lm/W Efficacy Ø 75 mm. Diameter Dimensions h 82,5 mm.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver On÷Off
Insulation class Class II

MECHANICAL CHARACTERISTICS

optical compartment IP rate IP40 recessed compartment IP rate IP20





Accent Drop

RTL19110 - Rounded Adjustable - 10 W - 900 lumen / 2700 K / CRI >90

HOLE RECESS DIMENSIONS

hole recess diameter Ø 65 mm.

a x b hole recess 75 x 75 mm.75 x 75 mm.

ENERGY CLASSIFICATION



This luminaire contains built-in LED lamps.



The lamps cannot be changed in the luminaire.

LED SOURCE DETAILS

led source typeCoB LedLED brandBridgeluxLED current250 mALED voltage36 V

Service lifetime L80 / B20 - 50.000 h.

Light temperature 2700 K
CRI CRI >90
SDCM <3

DRIVER CHARACTERISTICS

driver On÷Off
Operating temperature -20°C ÷ 45°C

LIGHTING DETAILS

emission rotationally symmetrical

luminous effect spot optic 15°
Beam angle – direct 15°
UGR < 16
Cut Hood 40°



Accent Drop

RTL19110 - Rounded Adjustable - 10 W - 900 lumen / 2700 K / CRI >90

PHOTOMETRIC

