

Accent Drop

RTL19120CA - Rounded Adjustable - 15 W - 1400 lumen / 3000 K / CRI >90

DESCRIPTION


Accent is the downlight equipped with the same LED modules of the Nemo series, it is ideal for all interior design projects where it is necessary to recreate well-defined light accents in the absence of glare. Accent has the LED source set back and completely hidden from view and with a 40 $^{\circ}$ cut-off it offers maximum visual comfort by creating precise and well-defined uniform light accents. The Drop version is ideal for spot effects on the horizontal plane while the Side version allows you to tilt the optical module for lateral light emissions. All versions are installed in a \emptyset 65 mm recessed hole.



Switch Casambi

PRODUCTS CHARACTERISTICS

installation type trimmed recessed **Aluminum** material White Color 15 W Power Lumen output - Full emission 1408 lm 94 lm/W Efficacy Ø 75 mm. Diameter Dimensions h 105,5 mm.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Casambi
Insulation class Class II

MECHANICAL CHARACTERISTICS

optical compartment IP rate IP40 recessed compartment IP rate IP20





Accent Drop

RTL19120CA - Rounded Adjustable - 15 W - 1400 lumen / 3000 K / CRI >90

HOLE RECESS DIMENSIONS

hole recess diameter

Ø 65 mm.

ENERGY CLASSIFICATION



contains built-in LED lamps.



The lamps cannot be changed

LED SOURCE DETAILS

led source type CoB Led LED brand Bridgelux 350 mA LED current LED voltage 36 V

L80 / B20 - 50.000 h. Service lifetime

3000 K Light temperature CRI CRI >90 **SDCM** < 3

DRIVER CHARACTERISTICS

driver Casambi -20°C ÷ 45°C Operating temperature

LIGHTING DETAILS

emission rotationally symmetrical luminous effect spot 15° optic

15° Beam angle - direct **UGR** < 17 Cut Hood 40°



Accent Drop

RTL19120CA - Rounded Adjustable - 15 W - 1400 lumen / 3000 K / CRI > 90

PHOTOMETRIC

