

Accent Drop

RTL19324PD - Squared Adjustable - 15 W - 1400 lumen / 4000 K / CRI >90

DESCRIPTION

Accent is the downlight equipped with the same LED modules of the Nemo series, it is ideal for all interior design projects where it is necessary to recreate well-defined light accents in the absence of glare. Accent has the LED source set back and completely hidden from view and with a 40 $^{\circ}$ cut-off it offers maximum visual comfort by creating precise and well-defined uniform light accents. The Drop version is ideal for spot effects on the horizontal plane while the Side version allows you to tilt the optical module for lateral light emissions. All versions are installed in a \emptyset 65 mm recessed hole.



Switch Pan Digital

PRODUCTS CHARACTERISTICS


installation type trimmed recessed material Aluminum

Color White
Power 15 W

Lumen output - Full emission 1494 Im

Efficacy 100 Im/W

Dimensions 75 x 75 mm.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Pan Digital
Insulation class Class II

MECHANICAL CHARACTERISTICS

optical compartment IP rate IP40 recessed compartment IP rate IP20





Accent Drop

RTL19324PD - Squared Adjustable - 15 W - 1400 lumen / 4000 K / CRI >90

HOLE RECESS DIMENSIONS

hole recess diameter

Ø 65 mm.

ENERGY CLASSIFICATION



This luminaire contains built-in LED lamps.



The lamps cannot be changed in the luminaire.

LED SOURCE DETAILS

led source typeCoB LedLED brandBridgeluxLED current350 mALED voltage36 V

Service lifetime L80 / B20 - 50.000 h.

Light temperature 4000 K
CRI CRI >90
SDCM <3

DRIVER CHARACTERISTICS

driver Pan Digital
Operating temperature -20°C ÷ 45°C

LIGHTING DETAILS

emission rotationally symmetrical

luminous effect flood optic 24°
Beam angle – direct 24°
UGR < 17
Cut Hood 40°



Accent Drop

RTL19324PD - Squared Adjustable - 15 W - 1400 lumen / 4000 K / CRI >90

PHOTOMETRIC

