

Accent Drop

RTL19326DM - Squared Adjustable - 15 W - 1400 lumen / 3000 K / CRI >90

DESCRIPTION

Accent is the downlight equipped with the same LED modules of the Nemo series, it is ideal for all interior design projects where it is necessary to recreate well-defined light accents in the absence of glare. Accent has the LED source set back and completely hidden from view and with a 40 ° cut-off it offers maximum visual comfort by creating precise and well-defined uniform light accents. The Drop version is ideal for spot effects on the horizontal plane while the Side version allows you to tilt the optical module for lateral light emissions. All versions are installed in a Ø 65 mm recessed hole.

Switch

1...10V / Push

PRODUCTS CHARACTERISTICS

installation type	trimmed recessed		
material	Aluminum		
Color	White		
Power	15 W		. 30°
Lumen output – Full emission	1278 lm		
Efficacy	85 lm/W		
Dimensions	75 x 75 mm.		105,5
			$\begin{tabular}{ c c c c c } \hline \end{tabular} \end{tabular}$
			75x75
		0,30	🕲 ø65 mm. 🙆 0,50

ELECTRICAL CHARACTERISTICS

feeding	220÷240 V
driver	110V / Push
Insulation class	Class II

MECHANICAL CHARACTERISTICS

optical compartment IP rate recessed compartment IP rate	IP40 IP20	
PAN International Srl	Tel. +39 055 80 59 336/7	This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to
Via G. Michelucci, 1	Fax +39 055 80 59 338	make technical changes without notice.
50028 Barberino Tavarnelle	panint@panint.it	
Firenze, Italy	www.panint.it	



Accent Drop

RTL19326DM - Squared Adjustable - 15 W - 1400 lumen / 3000 K / CRI >90

HOLE RECESS DIMENSIONS

hole recess diameter

Ø 65 mm.

ENERGY CLASSIFICATION



LED SOURCE DETAILS

CoB Led
Bridgelux
350 mA
36 V
L80 / B20 - 50.000 h.
3000 K
CRI >90
< 3

DRIVER CHARACTERISTICS

driver	110V / Push
Operating temperature	-20°C ÷ 45°C

LIGHTING DETAILS

rotationally symmetrical	
flood	
32 °	
32°	
< 17	
40 °	
	flood 32° 32° < 17

Datasheet



Accent Drop

RTL19326DM - Squared Adjustable - 15 W - 1400 lumen / 3000 K / CRI >90

PHOTOMETRIC

