

# Accent Side

RTL19416CA - Squared Adjustable - 10 W - 900 lumen / 2700 K / CRI >90

## **DESCRIPTION**

Accent is the downlight equipped with the same LED modules of the Nemo series, it is ideal for all interior design projects where it is necessary to recreate well-defined light accents in the absence of glare. Accent has the LED source set back and completely hidden from view and with a 40  $^{\circ}$  cut-off it offers maximum visual comfort by creating precise and well-defined uniform light accents. The Drop version is ideal for spot effects on the horizontal plane while the Side version allows you to tilt the optical module for lateral light emissions. All versions are installed in a  $\emptyset$  65 mm recessed hole.



Switch Casambi

#### PRODUCTS CHARACTERISTICS


installation type trimmed recessed material Aluminum

Color White
Power 10 W

Lumen output - Full emission 807 Im

Efficacy 81 Im/W

Dimensions 75 x 75 mm.



# **ELECTRICAL CHARACTERISTICS**

feeding 220÷240 V
driver Casambi
Insulation class Class II

#### MECHANICAL CHARACTERISTICS

optical compartment IP rate IP40 recessed compartment IP rate IP20





# **Accent Side**

RTL19416CA - Squared Adjustable - 10 W - 900 lumen / 2700 K / CRI >90

#### HOLE RECESS DIMENSIONS

hole recess diameter

Ø 65 mm.

## **ENERGY CLASSIFICATION**



This luminaire contains built-in LED lamps.



The lamps cannot be changed in the luminaire.

## LED SOURCE DETAILS

led source typeCoB LedLED brandBridgeluxLED current250 mALED voltage36 V

Service lifetime L80 / B20 - 50.000 h.

Light temperature 2700 K
CRI CRI >90
SDCM <3

#### **DRIVER CHARACTERISTICS**

driver Casambi
Operating temperature -20°C ÷ 45°C

# LIGHTING DETAILS

emission rotationally symmetrical

luminous effect flood optic 32°
Beam angle – direct 32°
UGR < 16
Cut Hood 40°



# **Accent Side**

**RTL19416CA** - Squared Adjustable - 10 W - 900 lumen / 2700 K / CRI >90

# **PHOTOMETRIC**

