

Moby

RTL30203CA - 24 W / 3000 K / CRI >90

DESCRIPTION

Projectors of the Moby series are designed to illuminate the display areas of commercial environments and shops: they are equipped with high efficiency electronic drivers and high color rendering CoB LEDs (CRI> 90 and SDCM <3) to enhance the colors of the illuminated objects thanks to an intense and bright light. The optical groups are made by combining specific lenses with mirrored reflectors with curved and progressive facets, in order to have a high optical efficiency with a perfect light diffusion. The Moby projectors offer the possibility of extracting the optical body or moving it back into the false ceiling, thus allowing maximum flexibility and orientation in pointing. The connection with the driver is of the "fast plug" type and the fixing clips allow a tool-free installation.



Switch Casambi

PRODUCTS CHARACTERISTICS

net weight

installation type

material

Color

Power

Lumen output - Full emission

Efficacy

Diameter

Recessed Spotlights

Aluminum

White


24 W

2288 Im

95 Im/W

140 mm.

0,74 kg.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Casambi
Insulation class Class II

MECHANICAL CHARACTERISTICS





Moby

RTL30203CA - 24 W / 3000 K / CRI >90

product IP rate IP40

HOLE RECESS DIMENSIONS

hole recess diameter ø 125 mm.

ENERGY CLASSIFICATION



This luminaire contains built-in LED lamps.



The lamps cannot be changed in the luminaire.

LED SOURCE DETAILS

led source typeCoB LedLED brandBridgeluxLED current600 mA

Service lifetime L80 / B20 - 50.000 h.

Light temperature 3000 K
CRI CRI >90
SDCM <3

DRIVER CHARACTERISTICS

driver Casambi
Operating temperature -20°C ÷ 45°C

LIGHTING DETAILS

emission rotationally symmetrical

luminous effect flood optic 24°
Beam angle – direct 24°





Moby

RTL30203CA - 24 W / 3000 K / CRI >90

PHOTOMETRIC

