

Moby

RTL30307CA - 33 W / 3000 K / CRI >90

DESCRIPTION

Projectors of the Moby series are designed to illuminate the display areas of commercial environments and shops: they are equipped with high efficiency electronic drivers and high color rendering CoB LEDs (CRI> 90 and SDCM <3) to enhance the colors of the illuminated objects thanks to an intense and bright light. The optical groups are made by combining specific lenses with mirrored reflectors with curved and progressive facets, in order to have a high optical efficiency with a perfect light diffusion. The Moby projectors offer the possibility of extracting the optical body or moving it back into the false ceiling, thus allowing maximum flexibility and orientation in pointing. The connection with the driver is of the "fast plug" type and the fixing clips allow a tool-free installation.



Switch Casambi

PRODUCTS CHARACTERISTICS

net weight

installation type

material

Color

Power

Lumen output - Full emission

Efficacy

Diameter

Recessed Spotlights

Aluminum

White

33 W

3180 Im

96 Im/W

158 mm.

0,86 kg.

18° 130



∅ ø145 mm.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V
driver Casambi
Insulation class Class II

MECHANICAL CHARACTERISTICS





Moby

RTL30307CA - 33 W / 3000 K / CRI >90

product IP rate IP40

HOLE RECESS DIMENSIONS

hole recess diameter ø 145 mm.

LED SOURCE DETAILS

led source type CoB Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED brand Bridgelux LED current 800 mA

Service lifetime L80 / B20 - 50.000 h.

Light temperature 3000 K
CRI CRI >90
SDCM <3

DRIVER CHARACTERISTICS

driver Casambi
Operating temperature -20°C ÷ 45°C

LIGHTING DETAILS

emission rotationally symmetrical

luminous effect wide optic 60°
Beam angle – direct 60°

PHOTOMETRIC





Moby

RTL30307CA - 33 W / 3000 K / CRI >90

