

Focus

RTL34111 - Rounded - Fix / 4,5 W / 3000 K / CRI >80

DESCRIPTION

Small and performing, the Focus series of recessed minispots create precise accents of light without glare thanks to the backward position of the LED source. In the fixed and adjustable versions, the Focus minispots emit bright light within a sharp and smudge-free beam with only 4.5 W of electricity absorption. The LEDs selected from the first labels and the body entirely made of die-cast aluminum ensure both a long life to the LED source and the constancy of its colorimetric characteristics over time (L80 / B20 at 50,000 hours). Focus is available in a matt white and matt black finish and complete of wired driver.

www.panint.it



Switch

Firenze, Italy

On÷Off

PRODUCTS CHARACTERISTICS

installation type	Recessed Spotlights	
material	Aluminum	
Color	White	
Power	4,5 W	6.5 I
Lumen output – Full emission	195 lm	51
Efficacy	78 lm/W	
Diameter	ø 40 mm.	
Dimensions	h 51 mm.	
net weight	0,10 kg.	
		ø40
		₿ ø35 mm.
		2
		kg 0,10

ELECTRICAL CHARACTERISTICS						
driver	On÷Off					
MECHANICAL CHARACTERISTICS						
product IP rate	IP40					
HOLE RECESS DIMENSIONS						
PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.				

Uploaded 13/06/23 - pg 1 / 2



Focus

RTL34111 - Rounded - Fix / 4,5 W / 3000 K / CRI >80

hole recess diameter	ø 35 mm.

LED SOURCE DETAILS

led source type	Power Led
Photobiological risk	RG 1 Low risk (IEC 62471)
LED current	700 mA
Light temperature	3000 K
CRI	CRI >80
SDCM	< 3
SDCM	< 3

DRIVER CHARACTERISTICS

driver	On÷Off	
LIGHTING DETAILS		
luminous effect optic Beam angle – direct	spot 20° 20°	

PHOTOMETRIC

