

Focus

RTL34114 - Rounded - Fix / 4,5 W / 4000 K / CRI >80

DESCRIPTION

Small and performing, the Focus series of recessed minispots create precise accents of light without glare thanks to the backward position of the LED source. In the fixed and adjustable versions, the Focus minispots emit bright light within a sharp and smudge-free beam with only 4.5 W of electricity absorption. The LEDs selected from the first labels and the body entirely made of die-cast aluminum ensure both a long life to the LED source and the constancy of its colorimetric characteristics over time (L80 / B20 at 50,000 hours). Focus is available in a matt white and matt black finish and complete of wired driver.



Switch

On÷Off

PRODUCTS CHARACTERISTICS

installation type	Recessed Spotlights	
material	Aluminum	
Color	White	
Power	4,5 W	
Lumen output - Full emission	220 lm	51
Efficacy	88 lm/W	
Diameter	ø 40 mm.	
Dimensions	h 51 mm.	
net weight	0,10 kg.	
		ø40
		ⓓ ø35 mm.
		0 000 mm.
		2
		kg 0,10

ELECTRICAL CHARACTERISTICS			
driver	On÷Off		
MECHANICAL CHARAC	TERISTICS		
product IP rate	IP40		
HOLE RECESS DIMENSI	ONS		
PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.	

50028 Barberino Tavarnelle Firenze, Italy

panint@panint.it www.panint.it

Uploaded 13/06/23 - pg 1 / 2



Focus

RTL34114 - Rounded - Fix / 4,5 W / 4000 K / CRI >80

hole recess diameter	ø 35 mm.
	000 11111

LED SOURCE DETAILS

Power Led		
RG 1 Low risk (IEC 62471)		
700 mA		
4000 K		
CRI >80		
< 3		
	RG 1 Low risk (IEC 62471) 700 mA 4000 K CRI >80	

DRIVER CHARACTERISTICS

driver	On÷Off		
LIGHTING DETAILS			
luminous effect	spot		
optic	38°		
optic Beam angle - direct	38°		

PHOTOMETRIC

